

Job Name:	
Tag#	



Submittal Data Sheet	CTX12AXVJU
1.0-Ton Wall Mounted Indoor Unit	



Indoor Specifications				
	Cooling		Heating	
	H	M	H	M
Airflow Rate (cfm)	430	340	430	340
	L	SL	L	SL
	249	142	249	195
Sound (dBA) H / M / L / SL	46 / 39 / 30 / 19		45 / 38 / 29 / 24	
Dimensions (H x W x D) (in)	11-1/3 x 30-29/32 x 9-27/32			
Weight (Lbs)	20			
Nominal Capacity (Btu/hr)	12,000			

*See Outdoor Unit for Rated Capacities

Complete warranty details available from your local dealer or at www.daikincomfort.com. To receive the 10-Year Parts Limited Warranty, online registration must be completed within 60 days of installation. Online registration is not required in California or Quebec. If product is installed in a commercial application, limited warranty period is 5 years.

Piping	
Liquid (in)	1/4
Gas (in)	3/8
Drain (in)	3/4


Electrical		
	Cooling	Heating
Running Current (Rated) (A)	.17	.17
Power Consumption (Rated) (W)	38	38

Optional Accessories

Included	Part Number	Description
	AZAI6WSCDKB	DKN Residential Cloud Wi-Fi Adaptor for Single- and Multi-Zone System (S21)
	BRC944B2	Wired Remote Controller
	BRCW901A08	Wired Remote Controller Cable – 25ft
	BRCW901A03	Wired Remote Controller Cable – 10ft
	DACA-CP1-1	Inline Condensate Pump (Fits inside all Daikin wall & floor mount units)
	DACA-CP4-1	External Condensate Pump

Model : CTX07/09/12A

FOR ILLUSTRATIVE PURPOSES ONLY



3P621387-1

Note: Dimension in inch (mm)