



Submittal Data Sheet
 0.75-Ton Ceiling Mounted Cassette and Heat Pump
 FFQ09W2VJU9RX09WMVJU9

MODEL	Indoor Unit		FFQ09W2VJU9	
	Outdoor Unit		RX09WMVJU9	
			Cooling	Heating
Power Supply			1 ϕ , 208 - 230 V, 60 Hz	
Capacity Rated (Min. - Max.)	Btu/h	9,100 (4,600 - 11,000)	10,000 (4,600 - 14,000)	
Running Current (Rated)	A	3.94 - 3.56	3.74 - 3.38	
Power Consumption (Rated)	W	758 - 758	698 - 698	
Power Factor (Rated)	%	92.5 - 92.5	89.7 - 89.9	
SEER2 / HSPF2		19.80	9.40	
EER2 (Rated)	Btu/h·W	12.00	—	
COP2 (Rated)	W/W	—	4.20	
Piping Connections	Liquid	in. (mm)	ϕ 1/4 (6.4)	
	Gas	in. (mm)	ϕ 3/8 (9.5)	
	Drain	in. (mm)	VP20 (O.D. ϕ 1-1/32 (26))	
Heat Insulation		Both Liquid and Gas Pipes		
Max. Interunit Piping Length	ft (m)	65-5/8 (20)		
Max. Interunit Height Difference	ft (m)	49-1/4 (15)		
Chargeless	ft (m)	32-3/4 (10)		
Amount of Additional Charge of Refrigerant	oz/ft (g/m)	0.21 (20)		
Indoor Unit		FFQ09W2VJU9		
Decoration Panel (1)	Model (Color)		BYFQ60B3W1 (White)	
	Dimensions (H \times W \times D)	in. (mm)	2-3/16 \times 27-9/16 \times 27-9/16 (55 \times 700 \times 700)	
	Weight (Mass)	lbs (kg)	6.0 (2.7)	
Decoration Panel (2)	Model (Color)		BYFQ60C2W1W (White) / BYFQ60C2W1S (Silver)	
	Dimensions (H \times W \times D)	in. (mm)	1-13/16 \times 24-7/16 \times 24-7/16 (46 \times 620 \times 620)	
	Weight (Mass)	lbs (kg)	6.2 (2.8)	
Heat Exchanger	Rows \times Stages, Fin per Inch		2 \times 16, 21	
	Fin Spec / Tube		Slit Fin / ϕ 5 Hi-XA Tube	
Airflow Rate	H / M / L	cfm	378 / 339 / 268	399 / 357 / 282
		m3/min	10.7 / 9.6 / 7.6	11.3 / 10.1 / 8.0
Fan	Type / Speed		Turbo Fan / 3 Steps	

Daikin Comfort Technologies North America, Inc 19001 Kermier Rd Waller TX 77484
 Daikin City Generated Submittal Data www.daikincomfort.com or www.daikinac.com

(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications, and information in this data sheet without notice and without incurring any obligations)




Submittal Data Sheet
 0.75-Ton Ceiling Mounted Cassette and Heat Pump
 FFQ09W2VJU9RX09WMVJU9

Running Current (Rated)		A	0.23 - 0.21	0.23 - 0.21
Power Consumption (Rated)		W	23 - 23	23 - 23
Power Factor (Rated)		%	48.1 - 47.6	48.1 - 47.6
Temperature Control		Microcomputer Control		
Dimensions (H × W × D)		in. (mm)	10-1/4 × 22-5/8 × 22-5/8 (260 × 575 × 575)	
Weight (Mass)		lbs (kg)	36 (16)	
Sound Pressure Level	H / M / L	dB(A)	38 / 35 / 29	38 / 35 / 29
Remote Controller (Option)		Wired	BRC1E73	
		Wireless	BRC082A41W / BRC082A42W / BRC082A42S	
Outdoor Unit		RX09WMVJU9		
Casing Color		Ivory White		
Heat Exchanger	Fin Spec / Tube		Waffle Fin (PE) / φ 7 Hi-XSL Tube	
Fan Motor	Motor Output	HP	0.03	
Compressor	Type		Hermetically Sealed Swing Type	
	Model		1YC23AUXD	
Refrigerant Oil	Type		FVC50K	
	Charge	oz (L)	12.68 (0.375)	
Refrigerant	Type		R-410A	
	Charge	lbs (kg)	2.09 (0.95)	
Airflow Rate		cfm (m ³ /min)	985 (27.9)	1,144 (32.4)
Fan	Type		Propeller	
Running Current (Rated)		A	3.71 - 3.35	3.51 - 3.17
Power Consumption (Rated)		W	735 - 735	675 - 675
Power Factor (Rated)		%	95.2 - 95.4	92.5 - 92.6
Dimensions (H × W × D)		in. (mm)	21-5/8 × 26-9/16 × 11-3/16 (550 × 675 × 284)	
Weight (Mass)		lbs (kg)	63 (29)	
Sound Pressure Level		dB(A)	46	50
Conditions Based on	Indoor		80.0°FDB (26.7°CDB) / 67.0°FWB (19.4°CWB)	70.0°FDB (21.1°CDB) / 60.0°FWB (15.6°CWB)
	Outdoor		95.0°FDB (35.0°CDB) / 75.0°FWB (24.0°CWB)	47.0°FDB (8.3°CDB) / 43.0°FWB (6.1°CWB)
	Piping Length		25 ft (7.5 m)	
Note(s)		SL: The quiet fan level of the airflow rate setting.		

Daikin Comfort Technologies North America, Inc 19001 Kermier Rd Waller TX 77484
 Daikin City Generated Submittal Data www.daikincomfort.com or www.daikinac.com


(Daikin's products are subject to continuous improvements. Daikin reserves the right to modify product design, specifications, and information in this data sheet without notice and without incurring any obligations)

FFQ09/12/15/18W2VJU9 with BYFQ60B3W1 (Decoration Panel)




C: 3D106040A

FFQ09/12/15/18W2VJU9 with BYFQ60C2W1W(S) (Decoration Panel)




C: 3D106039A

4.2 Outdoor Unit RX09/12WMVJU9



3D136777

RX15/18WMVJU9



3D092224D

11. Electric Characteristics

Indoor Unit	Outdoor Unit	Power Supply				Compressor	OFM			IFM		
		Hz - Volts	Voltage Range	MCA	MFA		RLA	Hp	W	FLA	Hp	W
FTXR09WVJUW9 FTXR09WVJUS9	RX09WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.6	15	7.5	0.03	20	0.17	0.04	29	0.13
FTXR12WVJUW9 FTXR12WVJUS9	RX12WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.7	15	7.5	0.03	20	0.17	0.04	29	0.19
FTXR18WVJUW9 FTXR18WVJUS9	RX18WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	11.0	15	10.8	0.12	93	0.58	0.04	29	0.21
FDMQ09WVJU9	RX09WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.0	15	7.5	0.03	20	0.17	0.17	130	0.49
FDMQ12WVJU9	RX12WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.1	15	7.5	0.03	20	0.17	0.17	130	0.63
FDMQ15WVJU9	RX15WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.6	15	8.0	0.10	75	0.47	0.31	230	0.64
FDMQ18WVJU9	RX18WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	11.6	15	10.8	0.12	93	0.58	0.31	230	0.84
FDMQ24WVJU9	RX24WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	13.1	20	12.0	0.12	93	0.58	0.31	230	1.10
FFQ09W2VJU9	RX09WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.8	15	7.5	0.03	20	0.17	0.07	50	0.28
FFQ12W2VJU9	RX12WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	7.8	15	7.5	0.03	20	0.17	0.07	50	0.28
FFQ15W2VJU9	RX15WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	8.3	15	8.0	0.10	75	0.47	0.07	50	0.28
FFQ18W2VJU9	RX18WMVJU9	60 Hz - 208 V 60 Hz - 230 V	Max. 60 Hz, 253 V Min. 60 Hz, 187 V	11.0	15	10.8	0.12	93	0.58	0.07	50	0.28

Symbols:

MCA	: Min. circuit amps	(A)
MFA	: Max. fuse amps	(A)
RLA	: Rated load amps	(A)
OFM	: Outdoor fan motor	
IFM	: Indoor fan motor	
FLA	: Full load amps	(A)
W / Hp	: Fan motor rated output	(W, Hp)

Notes:

1. RLA is the max current that comes in cooling operation and heating operation.
2. Maximum allowable voltage variation between phases is 2%.
3. Select wire size based on the larger value of MCA.

C: 3D143137

C: 3D143129