



Part Number	Optional Accessories for Indoor Unit	Part Number	Optional Accessories for Outdoor Unit
BRC944B2-A08	Wired Remote Controller (Requires 1 cord below)	KPW063B4	Air Direction Adjustment Grille
BRCW901A03	Wired Remote Controller Cord (Shielded wire) 9.8 ft	KKG063A42	Back Protection Wire Net
BRCW901A08	Wired Remote Controller Cord (Shielded wire) 26.3 ft	KKP937A4	Drain Plug - Standard
KAF970A48	Titanium Apatite Deodorizing Filter (Without frame) Standard	KEH063A4E	Drain Pan Heater
KKF910AA4	Remote Controller Loss Prevention with Chain	KPS063A41	Snow Hood (Intake side panel)
DTST-LTE-LA-A	Daikin <i>ONE</i> Lite smart thermostat	KPS063A44	Snow Hood (Intake side panel)
DTST-CWBSA-NI-B +DAPT-ONE-VMS	Daikin <i>ONE</i> + smart thermostat		
DTST-TOU-A+ DAPT-ONE-VMS	Daikin <i>ONE</i> Touch smart thermostat		
AZAI6WSCDKB	DKN Residential Cloud Wi-Fi Adaptor		
AZAI6WSPDKC	Daikin <i>DKN Plus</i> Interface		

Cooling only System

Model	Indoor Unit		FTXV30AVJU9	FTXV36AVJU9
	Outdoor Unit		RKV30AVJU9	RKV36AVJU9
Cooling capacity rated (Min. ~ Max.)	Btu/h		31,400 (10,200 ~ 31,400)	34,400 (10,200 ~ 34,400)
EER2 Rated			10	9.8
SEER2			19	18
Piping Connections	Liquid	in. (mm)	Ø 1/4 (Ø 6.4)	
	Gas		Ø 5/8 (Ø 16.0)	
	Drain		Ø 5/8 (Ø 16.0)	
Max. Interunit Piping Length			98-1/2 (29.8)	
Max. Interunit Height Difference	ft. (m)		65-5/8 (20)	
Chargeless			32-3/4 (10)	
Amount of Additional Charge of Refrigerant	oz/ft (g/m)		0.22 (20)	
Operating Range - Cooling			50° - 115°F	
Operating Range - Enhanced Cooling*			14° - 115°F	
Operating Range - Low Ambient Cooling**			-4° - 115°F	
Operating Range - Ultra Low Ambient Cooling***			-22° - 115°F	
Airflow Rate	Indoor Unit		FTXV30AVJU9	FTXV36AVJU9
	H	cfm (m³/min)	925	971
	M		784	794
	L		600	600
SL	533		533	
Fan	Speed	Steps	1,250 / 1,100 / 880 / 800	
Air Direction Control			Right, Left, Horizontal, Downward	
Air Filter			Removable, Washable	
Dimensions (H × W × D)	in. (mm)		12-15/16 × 48-13/16 × 10-15/16 329 × 1,240 × 278	
Weight	lbs. (kg)		42(19)	
Sound Pressure Level (H / M / L / SL)	dB(A)		53 / 47 / 40 / 37	54 / 47 / 40 / 37
Refrigerant	Outdoor Unit		RKV30AVJU9	RKV36AVJU9
	Type		R-32	
	Charge	lbs. (kg)	3.68 (1.67)	3.68 (1.67)
Airflow Rate	H	cfm (m³/min)	73.2 (2,585)	81.3 (2,871)
	SL		—	—
Dimensions (H × W × D)	in. (mm)		29-1/2 × 34-1/4 × 12-5/8 750 × 870 × 320	
Weight	lbs. (kg)		128 (58)	128 (58)
Sound Pressure Level	H	dB(A)	57	60

*Activated with a dipswitch setting. Refer to installation manual for more details.

**Activated with a dipswitch setting and use of air direction adjustment grille (KPW063B4). Refer to installation manual for more details.

***Activated with additional dipswitch setting and notes per **. Refer to installation manual for more details.

Unit Combination		Power Supply				Fan/Compressor		Indoor Fan
INDOOR UNIT	OUTDOOR UNIT	Hz - VOLTS	VOLTAGE RANGE	MCA	MOP	INVERTER DRIVE INPUT	INVERTER DRIVE INPUT	
FTXV30AVJU9	RKV30AVJU9	60 - 208	Min. 187 V Max. 253 V	21.8	25	17.5	0.39	
		60 - 230						
FTXV36AVJU9	RKV36AVJU9	60 - 208	Min. 187 V Max. 253 V	21.9	25	17.6	0.39	
		60 - 230						